

Insurance Appraisals | Reserve Studies | Wind Mitigation

COMMERCIAL WINDSTORM MITIGATION INSPECTION REPORT (OIR-B1-1802)

Prepared for:

Windrush Bay Condominium Association, Inc.

10 Windrush Bay Dr Tarpon Springs, FL 34689

As of 10/5/2015





Felten Professional Adjustment Team, LLC 701 Enterprise Rd. E., Suite 704 Safety Harbor, FL 34695 Office 866.568.7853 Fax 866.804.1052 www.FPATadjusters.com



SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES FPAT File #MUD157124 LOCATED AT: 10 Windrush Bay Dr

RECAPITULATION OF MITIGATION FEATURES For 10 Windrush Bay Dr

1. <u>Building Code:</u> Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1983 per Pinellas County

Property Appraiser.

2. Roof Covering: FBC Equivalent

Comments: The roof covering was replaced in 2003. The roof permit was

confirmed and the permit number is 03-107. This roof was verified as meeting the building code requirements outlined on the mitigation

affidavit.

3. Roof Deck Attachment: Level A

Comments: Inspection verified 1/2" plywood roof deck attached with staples at a

minimum of 6" on the edge & 12" in the field.

4. Roof to Wall Clips

Attachment:

Comments: Inspection verified embedded straps fastened with a minimum of

three nails.

5. Roof Geometry: Other Roof

Comments: Inspection verified a gable roof shape.

6. <u>SWR:</u> No

Comments: Inspection verified no secondary water resistance.

7. **Opening Protection:** None or Some Glazed Openings

Comments: Inspection verified no opening protection.



Address Verification




Roof Covering (Section 2)



Roof Deck Attachment (Section 3)

SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 10 Windrush Bay Dr





Roof to Wall Attachment (Section 4)



Roof Shape (Section 5)



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Maintain a copy of this form and any documentation provided with the insurance poncy					
Inspection Date: 10/5/2015					
Owner Information					
Owner Name: Windrush Bay Cor	ndominium Association, Inc.	Contact Person: Louis De Santis			
Address: 10 Windrush Bay Dr		Home Phone:			
City: Tarpon Springs Zip: 34689		Work Phone: (727) 726-8000			
County: Pinellas	County: Pinellas Cell Phone:				
Insurance Company:	·	Policy #:			
Year of Home: 1983	# of Stories: 1	Email:			

Teal of Hollie. 1903	# 01 Stories.	1	Ellian.	
NOTE: Any documentation used in va accompany this form. At least one pho though 7. The insurer may ask addition	otograph must ac	company this form	ı to validate each attribute n	narked in questions 3
 Building Code: Was the structure by the HVHZ (Miami-Dade or Broward A. Built in compliance with the FBC: 3/1/2002: Building Permit Applie B. For the HVHZ Only: Built in comprovide a permit application with C. Unknown or does not meet the results. 	Counties), South F Year Built . For cation Date (MM/DD/ bliance with the SF to a date after 9/1/1	Florida Building Coo homes built in 2002 YYYY) FBC-94: Year Built 994: Building Perm	de (SFBC-94)? ½2003 provide a permit applic For homes built in 1	ation with a date after 994, 1995, and 1996
2. Roof Covering: Select all roof cover OR Year of Original Installation/Rep covering identified.				
2.1 Roof Covering Type:	Date	Product Approval #	Replacement	Compliance
 [X] 1. Asphalt/Fiberglass Shingle [] 2. Concrete/Clay Tile [] 3. Metal [] 4. Built Up [] 5. Membrane [] 6. Other 	1/21/2003			0 0 0 0 0
 [X] A. All roof coverings listed above a installation OR have a roofing p [] B. All roof coverings have a Miami-permit application after 9/1/199 [] C. One or more roof coverings do not [] D. No roof coverings meet the requir 3. Roof Deck Attachment: What is the 	permit application Dade Product App. 4 and before 3/1/2 t meet the requirer ements of Answer	date on or after 3/1/ roval listing current 002 OR the roof is onents of Answer "A" or "B".	02 OR the roof is original and at time of installation OR (for original and built in 1997 or la " or "B".	built in 2004 or later. the HVHZ only) a roofing
[X] A. Plywood/Oriented strand board of staples or 6d nails spaced at 6" ale -OR- Any system of screws, nai uplift less than that required for 0 [] B. Plywood/OSB roof sheathing with 24" inches o.c.) by 8d common nother deek festening system or the	(OSB) roof sheath ong the edge and 1: ils, adhesives, othe Options B or C bel th a minimum this ails spaced a maxi	ing attached to the r 2" in the fieldOR- er deck fastening sy low. ckness of 7/16"inch imum of 12" inches	oof truss/rafter (spaced a maxibatten decking supporting wo ystem or truss/rafter spacing that attached to the roof truss/rafter in the fieldOR- Any system	od shakes or wood shingles hat has an equivalent mean fter (spaced a maximum of of screws, nails, adhesives

- other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 10 Windrush Bay Dr., Tarpon Springs

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

182 psf.	
D. Reinforced	d Concrete Roof Deck.
[] E. Other:	
[] F. Unknown o	
[] G. No attic ac	ccess.
	Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within nside or outside corner of the roof in determination of WEAKEST type)
	[] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
	[] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
Minimal cond	ditions to qualify for categories B, C, or D. All visible metal connectors are:
	[X]Secured to truss/rafter with a minimum of three (3) nails, and [X]Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
[X] B. Clips	
	[X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
[] C. Single Wra	aps
	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
D. Double W	1
	[] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
	Anchor bolts structurally connected or reinforced concrete roof.
[] F. Other:	
[] G. Unknown	
[] H. No attic ac	ccess
	try: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of ture over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[] A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter:
[] B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
[X] C. Other Ro	
	Vater Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the
sheathin from wa	ng or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling atter intrusion in the event of roof covering loss.
[X] B. No SWR	
[] C. Unknown o	or undetermined.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least

Inspectors Initials Property Address 10 Windrush Bay Dr., Tarpon Springs

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Glazed Openings				Non-Glazed Openings	
		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure						
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection						

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N
or X in the table above
A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above

- [] <u>B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only)</u> All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 2 to 4.5 lb.)

B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

.]	C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB
	meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
	☐ C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
	☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 10 Windrush Bay Dr. Tarpon Springs

the table above

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

[] N. Exterior Opening Protection (unverified shutter sy protective coverings not meeting the requirements of protective coverings of compliance (Level N	of Answer "A", "B", or C" of					
"B" with no documentation of compliance (Level N in the table above).						
	 N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the 					
□ N.3 One or More Non-Glazed openings is classified as Lev	vel X in the table above					
[X] X. None or Some Glazed Openings One or more Glazed		vel X in t	he table above.			
MITIGATION INSPECTIONS MUST	DE CEDTIEIED DV 4 OUA	LIEIED	INCDECTOD			
Section 627.711(2), Florida Statutes, pro						
Qualified Inspector Name: John Felten	License Type: CBC		License or Certificate #: CBC1255984			
Inspection Company: Felten Professional Adjustment	Геаm, LLC.	Phone	: 866-568-7853			
Qualified Inspector – I hold an active license as a	a: (check one)					
Home inspector licensed under Section 468.8314, Florida Statutraining approved by the Construction Industry Licensing Board	tes who has completed the statu		er of hours of hurricane mitigation			
☐ Building code inspector certified under Section 468.607, Florid						
☐ General, building or residential contractor licensed under Section						
Professional engineer licensed under Section 471.015, Florida S						
Professional architect licensed under Section 481.213, Florida S						
Any other individual or entity recognized by the insurer as poss verification form pursuant to Section 627.711(2), Florida Statut		ons to prop	perty complete a uniform mitigation			
I, am a qualified inspector and I personally performed the inspection or (licensed contractors and professional engineers only) I had my employee (<u>Ian Wright</u>) perform the inspection and I agree to be responsible for his/her work. Qualified Inspector Signature:						
<u>Homeowner to complete</u> : I certify that the named Qualific residence identified on this form and that proof of identification						
Signature:	Date:					
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes) The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.						
Inspectors Initials Property Address 10 Windrush Ba	ay Dr, Tarpon Springs					

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.