Felten Professional Adjustment



Reserve Studies | Insurance Appraisals | Wind Mitigation

COMMERCIAL WINDSTORM MITIGATION REPORT (OIR-B1-1802)

Windrush Bay Condominium Association, Inc. 645-648 Windrush Bay Dr, Building N Tarpon Springs, FL 34689



As of 2/13/2020 FPAT File# MUD2013974

FELTEN PROFESSIONAL ADJUSTMENT TEAM 866.568.7853
www.FPATadjusters.com | info@FPATadjusters.com



RECAPITULATION OF MITIGATION FEATURESFor 645-648 Windrush Bay Dr, Building N

1. <u>Building Code:</u> Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1976 per Pinellas County

Property Appraiser.

2. Roof Covering: No roof coverings meet the minimum requirements

Comments: The roof covering was replaced in 2001. The roof permit was

confirmed and the permit number is 01-2287. This roof was verified as not meeting the building code requirements outlined on the

mitigation affidavit.

3. Roof Deck Attachment: Level A

Comments: Inspection verified 1/2" plywood roof deck attached with 6d nails at

a minimum of 6" on the edge & 12" in the field.

4. Roof to Wall Clips

Attachment:

Comments: Inspection verified hurricane clips fastened with a minimum of three

nails.

5. Roof Geometry: Other Roof

Comments: Inspection verified a gable roof shape.

6. <u>SWR:</u> No

Comments: Inspection verified no secondary water resistance.

7. **Opening Protection:** None or Some Glazed Openings

Comments: Inspection verified no opening protection.



Address Verification



Exterior Elevation

Roof Construction



SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 645-648 Windrush Bay Dr, Building N

FPAT File #MUD2013974

Roof Construction



Roof Construction



Roof Construction



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 2/13/2020						
Owner Information						
Owner Name: Windrush Bay Condominiu	Contact Person: Chris Stancil					
Address: 645-648 Windrush Bay Dr, Build	Home Phone:					
City: Tarpon Springs Zip: 34689		Work Phone: (727) 726-8000				
County: Pinellas	Cell Phone:					
Insurance Company:	Policy #:					
Year of Home: 1976	Email:					

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.

1.	Building Code : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in
	the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?
[]	A. Built in compliance with the FBC: Year Built . For homes built in 2002/2003 provide a permit application with a date after
	3/1/2002: Building Permit Application Date (MM/DD/YYYY)
[]	B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996
	provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)//
ſΧ	C. Unknown or does not meet the requirements of Answer "A" or "B"

2. **Roof Covering:** Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.

2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
[X] 1. Asphalt/Fiberglass Shingle	12/27/2001			
[] 2. Concrete/Clay Tile				[]
[] 3. Metal				[]
[] 4. Built Up				[]
[] 5. Membrane				[]
[] 6. Other				[]

- [] A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
- [] B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
- [] C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
- [X] D. No roof coverings meet the requirements of Answer "A" or "B".
- 3. **Roof Deck Attachment**: What is the weakest form of roof deck attachment?
- [X] A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 645-648 Windrush Bay Dr, Building N, Tarpon Springs

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FPAT File #MUD2013974

[] D. Reinforced Concrete R [] E. Other: [] F. Unknown or unidentific	
	<u>t</u> : What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within
	ide corner of the roof in determination of WEAKEST type)
top plate of	ter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the the wall, or nectors that do not meet the minimal conditions or requirements of B, C, or D
	nalify for categories B, C, or D. All visible metal connectors are:
[X]Secured [X]Attache the	to truss/rafter with a minimum of three (3) nails, and d to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe rosion.
[X] B. Clips	
[] Metal co	connectors that do not wrap over the top of the truss/rafter, or nnectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai juirements of C or D, but is secured with a minimum of 3 nails.
[] C. Single Wraps	
	connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a sum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
[] D. Double Wraps	
beam, on ei minimum o [] Metal con both sides, [] E. Structural Anchor bolts	nnectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond ther side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a f 2 nails on the front side, and a minimum of 1 nail on the opposing side, or nnectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on and is secured to the top plate with a minimum of three nails on each side.
[] F. Other:[] G. Unknown or unidentifi[] H. No attic access	ed
	the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall or enclosed space in the determination of roof perimeter or roof area for roof geometry classification).
	p roof with no other roof shapes greater than 10% of the total roof system perimeter. tal length of non-hip features: ; Total roof system perimeter:
[] B. Flat Roof Ro	of on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less an 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
	ny roof that does not qualify as either (A) or (B) above.
[] A. SWR (also called Seale sheathing or foam ac	ance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) ed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the lhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling in the event of roof covering loss.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least

Inspectors Initials Property Address 645-648 Windrush Bay Dr, Building N, Tarpon Springs

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.			Glazed Openings				Non-Glazed Openings	
			Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable- there are no openings of this type on the structure							
Α	A Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	C Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified							
IV	Other protective coverings that cannot be identified as A, B, or C							
Х	X No Windborne Debris Protection						·	

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

	☐ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
	☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
[]	B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings
	are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the
	product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for
	"Cyclic Pressure and Large Missile Impact" (Level B in the table above):

- ASTM E 1886 **and** ASTM E 1996 (Large Missile 4.5 lb.)
- SSTD 12 (Large Missile 4 lb. to 8 lb.)
- For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)

	☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
	☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
	☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
[]	C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with

plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
☐ C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
C 3 One or More Non Glazed openings is classified as Lavel N or Y in the table above

Inspectors Initials Property Address 645-648 Windrush Bay Dr, Building N, Tarpon Springs

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FP/	AΤ	File	#MU	D20	139	74

[] N. Exterior Opening Protection (unverified shutter syst protective coverings not meeting the requirements of					
"B" with no documentation of compliance (Level N i		•			
☐ N.1 All Non-Glazed openings classified as Level A, B, C, or	N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist				
☐ N.2 One or More Non-Glazed openings classified as Level E table above	in the table above, and no No	on-Glazed openings classified as Level X in the			
☐ N.3 One or More Non-Glazed openings is classified as Level	X in the table above				
[X] X. None or Some Glazed Openings One or more Glazed	openings classified and Lev	el X in the table above.			
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~				
Qualified Inspector Name: John Felten	License Type: CBC	License or Certificate #: CBC1255984			
Inspection Company: Felten Professional Adjustment Te	am, LLC.	Phone: 866-568-7853			
Qualified Inspector – I hold an active license as a:	(check one)				
☐ Home inspector licensed under Section 468.8314, Florida Statutes training approved by the Construction Industry Licensing Board a					
 □ Building code inspector certified under Section 468.607, Florida S □ General, building or residential contractor licensed under Section 					
$\ \square$ Professional engineer licensed under Section 471.015, Florida Sta	tutes.				
☐ Professional architect licensed under Section 481.213, Florida Sta	tutes.				
Any other individual or entity recognized by the insurer as posses verification form pursuant to Section 627.711(2), Florida Statutes		ns to properly complete a uniform mitigation			
under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. I, John Felten am a qualified inspector and I personally performed the inspection or (licensed)					
contractors and professional engineers only) I had my employand I agree to be responsible for his/her work.	yee (<u>James Sheets</u>) perfo	rm the inspection			
R. A.					
Qualified Inspector Signature: Date: 2/13/2020					
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection.					
Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative.					
Signature: Date:					
An individual or entity who knowingly provides or utters a sobtain or receive a discount on an insurance premium to who of the first degree. (Section 627.711(7), Florida Statutes) The definitions on this form are for inspection purposes only and cannot be	ich the individual or entit	y is not entitled commits a misdemeanor			
hurricanes.					

Inspectors Initials Property Address 645-648 Windrush Bay Dr. Building N. Tarpon Springs

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.