

Insurance Appraisals | Reserve Studies | Wind Mitigation

COMMERCIAL WINDSTORM MITIGATION INSPECTION REPORT (OIR-B1-1802)

Prepared for:

Windrush Bay Condominium Association, Inc.

39 Windrush Bay Dr Tarpon Springs, FL 34689

As of 10/5/2015









SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES FPAT File #MUD157124 LOCATED AT: 39 Windrush Bay Dr

RECAPITULATION OF MITIGATION FEATURES For 39 Windrush Bay Dr

1. <u>Building Code:</u> Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1984 per Pinellas County

Property Appraiser.

2. Roof Covering: FBC Equivalent

Comments: The roof covering was replaced in 2003. The roof permit was

confirmed and the permit number is 03-136. This roof was verified as meeting the building code requirements outlined on the mitigation

affidavit.

3. Roof Deck Attachment: Level A

Comments: Inspection verified 1/2" plywood roof deck attached with staples at a

minimum of 6" on the edge & 12" in the field.

4. Roof to Wall Clips

Attachment:

Comments: Inspection verified embedded straps fastened with a minimum of

three nails.

5. Roof Geometry: Other Roof

Comments: Inspection verified a gable roof shape.

6. <u>SWR:</u> No

Comments: Inspection verified no secondary water resistance.

7. **Opening Protection:** None or Some Glazed Openings

Comments: Inspection verified no opening protection.



Address Verification




Roof Covering (Section 2)



Roof Deck Attachment (Section 3)

SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 39 Windrush Bay Dr





Roof to Wall Attachment (Section 4)



Roof Shape (Section 5)



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 10/5/2015					
Owner Information					
Owner Name: Windrush Bay Condominium Association, Inc.		Contact Person: Louis De Santis			
Address: 39 Windrush Bay Dr		Home Phone:			
City: Tarpon Springs Zip: 34689		Work Phone: (727) 726-8000			
County: Pinellas		Cell Phone:			
Insurance Company:		Policy #:			
Year of Home: 1984 # of Stories: 1 Email:		Email:			

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.						
1. <u>Building Code</u> : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?						
[] A. Built in compliance with the FBC			2003 provide a permit applica	ation with a date after		
3/1/2002: Building Permit Appl [] B. For the HVHZ Only: Built in comprovide a permit application wit [X] C. Unknown or does not meet the r	pliance with the SF h a date after 9/1/19	BC-94: Year Built _ 994: Building Permi				
 Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified. 						
2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
[X] 1. Asphalt/Fiberglass Shingle	3/25/2003					
[] 2. Concrete/Clay Tile						
[] 3. Metal						
[] 4. Built Up			<u> </u>	[]		
[] 5. Membrane [] 6. Other				[]		
 [X] A. All roof coverings listed above installation OR have a roofing [] B. All roof coverings have a Miamipermit application after 9/1/19 [] C. One or more roof coverings do not [] D. No roof coverings meet the requirement. 	permit application of Dade Product Appr 34 and before 3/1/2 of meet the requiren	date on or after 3/1/0 roval listing current a 002 OR the roof is onents of Answer "A"	O2 OR the roof is original and at time of installation OR (for original and built in 1997 or la	built in 2004 or later. the HVHZ only) a roofing		
3. Roof Deck Attachment: What is the [X] A. Plywood/Oriented strand board staples or 6d nails spaced at 6" at	(OSB) roof sheathi	ing attached to the ro 2" in the fieldOR-	oof truss/rafter (spaced a maxi	od shakes or wood shingles		

- -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 39 Windrush Bay Dr., Tarpon Springs

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

182 psf.	
[] D. Reinforced Conc	rete Roof Deck.
[] E. Other:	
F. Unknown or unid	entified.
[] G. No attic access.	
5 feet of the inside of	Ehment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within or outside corner of the roof in determination of WEAKEST type)
[] A. Toe Nails	uss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the
	late of the wall, or
	etal connectors that do not meet the minimal conditions or requirements of B, C, or D
	·
	s to qualify for categories B, C, or D. All visible metal connectors are: ecured to truss/rafter with a minimum of three (3) nails, and
[X]Aı	ttached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
[X] B. Clips	
	Metal connectors that do not wrap over the top of the truss/rafter, or
	etal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail
positi [] C. Single Wraps	on requirements of C or D, but is secured with a minimum of 3 nails.
	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a
	ninimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
D. Double Wraps	
	tal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond
	, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a
	num of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
	tal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on
	sides, and is secured to the top plate with a minimum of three nails on each side.
	r bolts structurally connected or reinforced concrete roof.
[] F. Other: [] G. Unknown or unic	dentified
[] H. No attic access	Chunca
[] II. Ivo delle decess	
	That is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of ver unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[] A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.
1	Total length of non-hip features: ; Total roof system perimeter:
[] B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less
-	than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
[X] C. Other Roof	Any roof that does not qualify as either (A) or (B) above.
6. Secondary Water I	Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR)
	d Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the
	pam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling
	rusion in the event of roof covering loss.
[X] B. No SWR.	
[] C. Unknown or und	etermined.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least

Inspectors Initials Property Address 39 Windrush Bay Dr., Tarpon Springs

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Glazed Openings				Non-Glazed Openings	
		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure						
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection						

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N,
or X in the table above
A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above

- [] B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 2 to 4.5 lb.)

B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSE
meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
☐ C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 39 Windrush Bay Dr. Tarpon Springs

the table above

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter systems with no documentation) All Glazed openings are protected with					
protective coverings not meeting the requirements of Answer "A", "B", or C" or systems that appear to meet Answer "A" or "B" with no documentation of compliance (Level N in the table above).					
N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist					
 N.2 One or More Non-Glazed openings classified as Level D table above 	in the table above, and no Nor	n-Glazed	openings classified as Level X in the		
☐ N.3 One or More Non-Glazed openings is classified as Level	X in the table above				
[X] X. None or Some Glazed Openings One or more Glazed of	ppenings classified and Leve	el X in th	ne table above.		
MITIGATION INSPECTIONS MUST B. Section 627.711(2), Florida Statutes, provi					
Qualified Inspector Name: John Felten	License Type: CBC	.,,,,,,	License or Certificate #: CBC1255984		
Inspection Company: Felten Professional Adjustment Te	am, LLC.	Phone:	866-568-7853		
Qualified Inspector – I hold an active license as a:	(check one)				
Home inspector licensed under Section 468.8314, Florida Statutes training approved by the Construction Industry Licensing Board a			er of hours of hurricane mitigation		
\square Building code inspector certified under Section 468.607, Florida S					
☐ General, building or residential contractor licensed under Section					
Professional engineer licensed under Section 471.015, Florida Sta	tutes.				
Professional architect licensed under Section 481.213, Florida Sta					
Any other individual or entity recognized by the insurer as possess verification form pursuant to Section 627.711(2), Florida Statutes.		is to prop	erly complete a uniform mitigation		
Individuals other than licensed contractors licensed under S					
under Section 471.015, Florida Statues, must inspect the stru Licensees under s.471.015 or s.489.111 may authorize a direct					
experience to conduct a mitigation verification inspection.	et employee who possesses	the req	uisite skiii, kilowieuge, and		
I, John Felten am a qualified inspector and I	norsanally norfarmed the	incnecti	on or (licensed		
contractors and professional engineers only) I had my employ					
and I agree to be responsible for his/her work.	<u> </u>				
/ 2/					
R. A. C.					
Qualified Inspector Signature:Date	: <u>10/5/2015</u>				
An individual or entity who knowingly or through gross neg is subject to investigation by the Florida Division of Insuran					
appropriate licensing agency or to criminal prosecution. (Se	ction 627.711(4)-(7), Florid	da Statu	tes) The Qualified Inspector who		
certifies this form shall be directly liable for the misconduct	of employees as if the autl	norized 1	mitigation inspector personally		
performed the inspection.					
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification					
Signature:D	ate:				
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.					
Inspectors Initials Property Address 39 Windrush Bay Dr., Tarpon Springs					

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.